




Diesel Generator Set Data

Manufacturer:	Jiangsu Starlight Electricity Equipments Co.,Ltd
Set Type:	XG-150GF
Standby Power:	150KW/187.5KVA
Prime Power:	136KW/170KVA
Rated Current:	270 (A)
Rated Frequency:	50 (Hz)
Start-up time:	5~6 (s)
Power Factor:	0.8 (Lag)
Rated Voltage:	400/230 (V)

Standard Features

- ✓ Engine:DCEC Cummins 6CTA8.3-G2
- ✓ Radiator 40℃ max
- ✓ Fans are driven by belt, with safety guard
- ✓ 24V charge alternator
- ✓ Dry type air filter, fuel filter, oil filter
- ✓ Alternator: single bearing alternator
- ✓ IP23, insulation class H/H
- ✓ Main line circuit breaker
- ✓ Standard control panel
- ✓ Absorber
- ✓ muffle
- ✓ User manual





Diesel Engine Data

Manufacturer:	DCEC Cummins
Model:	6CTA8.3-G2
Prime/Standby Power:	163KW/180KW
Rated Speed:	1500 (r/min)
Cycle:	4 stroke
Cylinder Arrangement:	6 in line
Displacement:	8.3L
Bore and Stroke:	114*135 (mm)
Compression Ratio:	17:1
Governor Type:	Electronic
Start battery voltage:	24V DC

Air Intake System

Air Intake System:	Turbo, Water/Air Cooling
Max Intake Restriction:	6kPa
Burning Capacity:	12.4m ³ /min
Air Flow:	238m ³ /min

Exhaust System

Exhaust Gas Flow:	34.7m ³ /min
Exhaust Temperature:	570℃
Max Back Pressure:	10kPa

Fuel System

Fuel System:	PB type fuel pump
100%(Prime Power) Load:	215g/kwh

Oil System

Total Oil Capacity:	23.8L
Oil Consumption:	≤0.4g/kwh
Engine Oil Tank Capacity:	18.9L
Oil Pressure at Rated RPM:	276-414kPa

Cooling System

Cooling Way:	Water-cooled
Total Coolant Capacity:	34L
Thermostat:	82-95℃



Max Water Temperature:

104℃

Alternator Data

Manufacturer:	STARLIGHT
Excitation Mode:	Brushless and self- exciting
Number of phase and Access Act:	3-phase 4-wire
Connecting Type:	“Y” type connecting
Alternator Capacity:	187.5KVA
Alternator Efficiencies:	95%
Overload:	(PRP) 110% load can run 1h
Protection Level:	IP22-IP23
Insulation Class, Temperature Rise:	H/H
Telephone Influence Factor (TIF):	<50
THF:	<2%
Altitude:	≤1000m

Genset Electrical Performance

Voltage Regulation:	≥±5%
Voltage Regulation, Stead State:	≤±1%
Sudden Voltage Warp (100% Sudden Reduce):	≤+25%
Sudden Voltage Warp (Sudden Increase):	≤-20%
Voltage Stable Time (100% Sudden Reduce):	≤6S
Voltage Stable Time (Sudden Increase):	≤6S
Frequency Regulation, Stead State:	≤5%
Frequency Waving:	≤1.5%
Sudden Frequency Warp (100% Sudden Reduce):	≤+12%
Sudden Frequency Warp (Sudden Increase):	≤-10%
Frequency Recovery Time(100%Sudden Reduce):	≤5S
Frequency Recovery Time(Sudden Increase):	≤5S

Standard Control Panel



Starlight Standard Control Panel uses micro processing technique integrating digital, intelligent and network techniques which can carry out functions including auto start/stop, data measure, alarming. The controller uses LCD display, optional Chinese and English display interface with operation easy and reliable. It can be widely used in all types of generator automatic control system for compact structure, advanced circuits, simple connections and high reliability

Soundproof Type

Overall Size

3200(mm)*1400(mm)*1800(mm)

Weight

2750(kg)

